

KONICA MINOLTA VERTICAL CONTROL GRIP VC-7D

Specifications

Power	One or two NP-400 lithium, six AA-size Ni-MH Power source can be selected between the VC-7D and Maxxum 7D using power-source switch.
Battery Performance (with Fresh Batteries)	<p><u>Two NP-400 lithium</u></p> <ul style="list-style-type: none"> Approximately 800 frames. (CIPA measurement *1) Conforming to CIPA standard test method with a compact flash card. Approximately 1200 frames (Konica Minolta measurement A*2) Approximately 4000 frames (Konica Minolta measurement B*3) <p>Conditions: Anti-Shake: ON, Recording media: 512MB CompactFlash Card *1: CIPA: Camera & Imaging Products Association *2: Flash: OFF, other conditions are same as CIPA measurement. *3: Drive mode: 5 frames continuous shooting, Flash ;OFF, Instant Playback: NO, other conditions are same as CIPA measurement.</p> <p><u>Six AA-size Ni-MH (Rated at 2300mAh)</u></p> <ul style="list-style-type: none"> Approximately 300 frames. (CIPA measurement *1) Conforming to CIPA standard test method with a compact flash card. Approximately 450 frames (Konica Minolta measurement A *2) Approximately 1500 frames (Konica Minolta measurement B *3) <p>Conditions: Anti-Shake: ON, Recording media: 512MB CompactFlash Card *1: CIPA: Camera & Imaging Products Association *2: Flash: OFF, other conditions are same as CIPA measurement. *3: Drive mode: 5 frames continuous shooting, Flash ;OFF, Instant Playback: NO, other conditions are same as CIPA measurement. Condition: Battery performance will vary with usage conditions</p>
Dimensions (W x H x D)	5.71 x 3.17 x 1.89 inches (145 x 80.5 x 48mm)
Weight (Without Batteries)	9.35 ounces (265g)

Specifications are subject to change without notice.