## KONICA MINOLTA VERTICAL CONTROL GRIP VC-7D

## **Specifications**

Power	One or two NP-400 lithium, six AA-size Ni-MH
Tower	Power source can be selected between the VC-7D and Maxxum
	7D using power-source switch.
Battery Performance	Two NP-400 lithium
(with Fresh Batteries)	• Approximately 800 frames. (CIPA measurement *1)
(with Fresh Datteries)	Conforming to CIPA standard test method with a compact flash card.
	<ul> <li>Approximately 1200 frames (Konica Minolta measurement A*2)</li> </ul>
	• Approximately 4000 frames (Konica Minolta measurement B*3)
	Conditions: Anti-Shake: ON, Recording media: 512MB CompactFlash Card
	*1:CIPA: Camera & Imaging Products Association
	*2: Flash: OFF, other conditions are same as CIPA measurement.
	*3: Drive mode: 5 frames continuous shooting, Flash; OFF, Instant Playback: NO, other conditions are same as CIPA measurement.
	Six AA-size Ni-MH (Rated at 2300mAh)
	<ul> <li>Approximately 300 frames. (CIPA measurement *1)</li> <li>Conforming to CIPA standard test method with a compact flash card.</li> </ul>
	<ul> <li>Approximately 450 frames (Konica Minolta measurement A *2)</li> </ul>
	<ul> <li>Approximately 1500 frames (Konica Minolta measurement B *3)</li> </ul>
	Conditions: Anti-Shake: ON, Recording media: 512MB
	CompactFlash Card
	*1:CIPA:Camera & Imaging Products Association
	*2: Flash: OFF, other conditions are same as CIPA measurement.
	*3: Drive mode: 5 frames continuous shooting, Flash; OFF, Instant
	Playback: NO, other conditions are same as CIPA measurement.
	Condition: Battery performance will vary with usage conditions
Dimensions (W x H x D)	5.71 x 3.17 x 1.89 inches (145 x 80.5 x 48mm)
Weight (Without Batteries)	9.35 ounces (265g)

Specifications are subject to change without notice.