

MINOLTA DiIMAGE E201 DIGITAL CAMERA Specifications

CCD	1/1.75-type interline primary-color CCD with a total of 2.3 million pixels
Number of effective pixels	2.15 million
A/D conversion	12 bits
Sensitivity	Normal: ISO 85 equivalent High: ISO 340 equivalent
Aspect ratio	3:2
Focal length	8.2mm (35mm equivalent: 38mm)
Lens construction	5 elements in 4 groups (includes 3 elements with 4 aspheric surfaces)
Maximum aperture	f/3.0
Minimum Focus Distance	Approximately 2 ft. (0.6m)
Macro focus range	Approximately 1 ft. – 2 ft. (0.3 – 0.6 m) from the front of the lens
Viewfinder	Reversed Galilean viewfinder
Liquid Crystal Display (LCD)	46mm (1.8 inch) color monitor Total number of pixels: 77,000
Field of view	Approximately 90%
Shutter	CCD electronic shutter and mechanical shutter
Shutter speed	1/500 - 2 seconds
Autofocus	Video AF system
Focus lock	Available with pressing the shutter button part-way down
Metering	Center-weighted
Exposure modes	Programmed AE
Exposure compensation	+/- 2 EV in 1/2 increments
AE lock	Available with pressing the shutter button part-way down
Flash range	Approximately 2 ft. – 2.5 ft. (0.6 – 2.5 m) at ISO 85 equivalent Approximately 2 ft. – 16.4 ft. (0.6 – 5 m) at ISO 340 equivalent
Flash mode	Autoflash, Fill-flash, Flash cancel, Autoflash with red-eye reduction, Fill-flash with red-eye reduction, Macro (flash is cancelled)
Flash recycling time	Approximately 10 seconds
Continuous drive advance	Approximately 1 fps
Self-timer	Approximately 10-second delayed release
Remote control	IR Remote Control RC-3 (sold separately)
Movie recording	Movie clips with audio (maximum 60 seconds)
Color modes	Color, black and white
White balance	Automatic, Manual (Preset - Daylight, Fluorescent, Tungsten)
Sharpness settings	Three levels (Soft, Normal, Hard)
Digital zoom	2x, 1.4x
Delete function	Available (single frame or all frames)
Format function	Available in the setup mode
Image compression mode	Economy, Standard, Fine, Super fine
Number of pixels	Still images: 1792 x 1200 (full size), 800 x 600 (half size)
Storage capacity (8 MB) (Full File Size)	Super fine: 1 frame; Fine: 9 frames; Standard: 24 frames; Economy: 47 frames; Movie:40 seconds
File format	Exif 2.1 (JPEG, TIFF), Motion JPEG (AVI), DCF1.0-compliant, DPOF compliant (Supported by printing functions in version 1.1)
Exif tag information	Date and time, Shutter speed, Aperture value, Exposure compensation value, Flash on/off, Camera sensitivity, etc.
Recording medium	CompactFlash card Type I
PC interface	USB version 1.1

-more-

**DiMAGE S304 Specifications
(cont'd)**

Video output	NTSC, PAL (can be selected by user)
Audio signals	Tone indicates operation. Audio signal can be disabled.
Power	Four AA Alkaline or four AA Ni-MH batteries
Battery performance	Playback: 120 min. (approximately) with alkaline batteries Recording: 120 frames (approximately) (Based on Minolta's standard test method: alkaline batteries, LCD monitor on, flash used 50% of the frames, standard image quality, full-size images.)
External power source	6V DC with specified AC adapter (sold separately)
Dimensions (WxHxD)	4.46 x 2.5 x 2.3 inches (114 x 65 x 45 mm)
Weight	Approximately 7 ounces (210g) (without batteries and CompactFlash card)
System Requirements	IBM PC/AT compatible computer with preinstalled Windows ME, Windows 2000, Windows 98 or Windows 98 SE and a built-in USB port Power Macintosh G4 series, G3 series, iMac series, iBook or PowerBook G3 with preinstalled Mac OS 9.0 – 9.1 and a built-in USB port
Accessories	<i>Standard:</i> Hand Strap for DiMAGE E201 & Dimâge 2300 HS-DG201 Camera Case for DiMAGE E201 & Dimâge 2300 CS-DG201 USB Cable for DiMAGE E201 & Dimâge 2300 USB-300 Video Cable for DiMAGE E201 & Dimâge 2300 VC-200 CF Card (8 MB), AA Alkaline Batteries, CD-ROM for DiMAGE E201 CD-ROM for PhotoDeluxe Home Edition 4.0 Windows, CD-ROM for PhotoDeluxe 2.0 Macintosh <i>Optional:</i> IR Remote Control RC-3; AC Adapter AC-1L

Specifications, accessories and system requirements are subject to change without notice.

#