

MINOLTA ZOOM 160C DATE POINT AND SHOOT 35M CAMERA

Specifications

Camera type	35mm lens-shutter camera
Lens	Focal length: 37.5 – 160mm Construction: 6 elements in 6 groups (includes 2 double-sided aspheric elements) Maximum aperture: f/5.4 – f/12.4 Minimum focus distance: Wide: 2 ft. (0.6m) Telephoto: 3.1ft. (0.95m)
Viewfinder	Type: Real-image zoom viewfinder Field of view: 85% at 9.8 ft. (3m) Magnification: 0.37 – 1.46x Diopter: -1 at 16.4 ft. (5m)
Autofocus	Autofocus system: External, passive AF Focusing steps: 926 Focus lock: By pressing shutter-release button partway down
Autoexposure	Metering: 3-segment metering Control: Programmed AE Metering range (ISO 100): Wide: EV 3 – 17 / Telephoto: EV 4.1 – 17 Shutter speeds: 10 – 1/500 second ISO setting: Automatic with DX-coded film between ISO 25 - 3200 in 1 EV increments. <i>(ISO 25 with non-DX-coded film)</i>
Film transport	Automatic loading, Automatic rewind, Manual rewind Film chamber lock: Yes
Flash	Control: Electronic flashmatic with light intensity control Range: ISO 100: Wide: 2 – 15.1 ft. (0.6 – 4.6 m) Telephoto: 3.1 – 6.6 ft. (0.95 – 2 m) ISO 400: Wide: 2 – 30.2 ft. (0.6 – 9.2 m) Telephoto: 3.1 – 13.1 ft. (0.95 – 4 m) <i>* with color negative film</i> Flash modes: Autoflash (in low-light, back-light), Autoflash with red-eye reduction (in low-light, back-light), Fill-flash, Flash cancel, Night portrait (with red-eye reduction) Recycling time: Approximately 0.5 - 6.5 seconds
Continuous advance	Approximately 2.2 seconds per frame
Self-timer	10 seconds
Remote control	IR Remote Control RC-3 (sold separately)
Date imprinting	Year/month/day (Format can be changed.) Day/hour/minute Imprinting can be disabled.
Power	Battery: One 3V CR123A lithium battery Battery performance: Approximately fourteen 24-exposure rolls <i>Based on Minolta's standard test method: flash used with 50% of the exposures with a fresh battery</i>
Dimensions (WxHxD)	4.35 x 2.38 x 1.83 inches (110.5 x 60.5 x 46.5mm)
Weight	6.7 oz. (190 g) without battery

Specifications are subject to change without notice.

#