

MINOLTA ACTIVA D WP XL BINOCULARS

Specifications

	8x25 D WP XL	10x25 D WP XL	8x42 D WP XL	10x42 D WP XL
Prism type	Roof prism BaK4	Roof prism BaK4	Roof prism BaK4	Roof prism BaK4
Optical coatings: Optical surfaces – Prism surfaces	Fully multi-coated Phase coating Super reflective coating	Fully multi-coated Phase coating Super reflective coating	Fully multi-coated Phase coating Super reflective coating	Fully multi-coated Phase coating Super reflective coating
Magnification	8x	10x	8x	10x
Objective diameter	25mm	25mm	42mm	42mm
Angle of view	5.5°	5°	6.3°	6°
Apparent angle of view	44°	50°	50°	60°
Exit pupil	3.1mm	2.5mm	5.3mm	4.2mm
Eye relief	18mm (long)	17mm (long)	19mm (long)	15mm (long)
Brightness	9.8	6.3	27.6	17.6
Field at 1000 yards (Field at 1000m:)	288 ft. (96m)	262 ft. (87m)	330 ft. (110m)	314 ft. (105m)
Minimum focus distance	6.6 ft. / 2m	6.6 ft. / 2m	8.2 ft. / 2.5m	8.2 ft. / 2.5m
Interpupillary range	55 - 72mm	55 - 72mm	59 - 72mm	59 - 72mm
Dimensions (WxHxD)	28 x 4.25 x 1.81 inches (71 x 108 x 46mm)	28 x 4.25 x 1.81 inches (71 x 108 x 46mm)	5 x 5.71 x 2.2 inches (127 x 145 x 56mm)	5 x 5.71 x 2.2 inches (127 x 145 x 56mm)
Weight	10.8 oz. (305g)	10.8 oz. (305g)	21.9 oz. (620g)	22 oz. (625g)

Minolta and Activa are trademarks or registered trademarks of Minolta Co., Ltd.
All other brand and product names are trademarks or registered trademarks of their respective owners.

Specifications are subject to change without notice.

#